

Pharmaceutical
Multiphase Reactors
CHE.782

Design of Multiphase
Flow Processes
669.266

3

Theory-General Background on Closure Models and Spatial Filtering


Ass.Prof. Dr. Stefan Radl,
MSc. Federico Municchi
Email: radl@tugraz.at
Institute for Process and
Particle Engineering
Inffeldgasse 13/III
TU Graz

A part of this teaching material has been
prepared for NanoSim (<http://sintef.no/NanoSim/>)



NanoSim

NanoSim - A Multi-scale Simulation-Based Design Platform



To solve the transport equations on (affordable) coarse grids we need to take into account transport phenomena occurring at sub-grid scales by mean of closure models («**material relations**»¹⁾)

Closure models can be derived by **filtering «resolved» simulations**

Van Der Hoef et al. 2006, Multiscale modeling of Gas-Fluidized beds, Advances in chemical engineering.

¹https://ec.europa.eu/research/industrial_technologies/pdf/review_of_materials_modelling_iv.pdf

Favre average

- Used when filtering multiphase transport equations (A.Favre,1992)
- Favre variables are mass-weighted variables. A Favre averaged variable is defined as:

$$\tilde{\psi} = \frac{\overline{\rho\psi}}{\bar{\rho}}$$

In the case of an incompressible multiphase flow:

$$\tilde{\psi}_p(\mathbf{x}, t) = \frac{\int K(\mathbf{x} - \mathbf{z}, t - t') \phi_p(\mathbf{z}, t') \psi_p(\mathbf{z}, t') d\mathbf{z} dt'}{\int K(\mathbf{x} - \mathbf{z}, t - t') \phi_p(\mathbf{z}, t') d\mathbf{z} dt'}$$

Where the subscript p indicates a phase variable and ϕ_p is the phase volume fraction.


Favre Variance

$$\text{Var}(u_i) = \overline{u_i u_j} - \widetilde{u_i} \widetilde{u_j}$$


- It equivalent to the **sub-grid** stress tensors and fluxes
- Provides a quantitative measurement for the **dispersion** of the filtered quantity
- Further information can be found in *etc/doc/pdf/Finch_2009_IncrementalCalculationWeightedMeanVariance.pdf* for a complete description of the statistical tools used in CPPPO including running statistics

Approach

1. Typical flow regime laminar. So, take as reference force **Stokes drag force**.



$$F_d = 3\pi d_p u, \quad u \rightarrow 0$$



$$F_d \approx 0.44 A \frac{1}{2} \pi d_p^2, \quad u \uparrow \uparrow$$

\swarrow
 $\frac{1}{4} \pi d_p^2$

Approach

2. This yields already the most important **velocity, time, and length scales** that characterize the system behavior

$$u_t = \frac{d_p^2 \rho_p g}{18 \eta_f}$$

$$\tau_{relax} = \frac{d_p^2 \rho_p}{18 \eta_f}$$

$$L_{ref} = \frac{u_t^2}{g}$$

- All based on Stokes drag force (typically okay for particles with $d_p < 50 \mu\text{m}$)
- Often the Schiller-Naumann drag law is used to better estimate u_t

$$C_D = C_{D,Stk} f(Re_p) = \frac{24}{Re_p} (1 + 0.15 Re_p^{0.687})$$

$$Re_p = \frac{u d_p \rho_f}{\eta_f}$$

Approach

3. Define drag correction factor, and choose u to be the **superficial velocity**

$$F_d = F(\phi)3\pi\mu d_p u, \quad u \rightarrow 0$$

Dimensionless drag force $\longrightarrow F(\phi) = \frac{F_d}{3\pi\mu d_p u}$

4. However, obviously the **true (mean) velocity of the fluid $\langle u \rangle$** will be of relevance (analogy to flow through a network of pipes)

$$\langle u \rangle = \frac{u}{1 - \phi}$$

5. For the Reynolds number, however, we use the **superficial velocity**

$$Re_p = \frac{|\langle u_{rel} \rangle|(1 - \phi)d_p \rho_f}{\eta_f}$$

Approach

6. Come up with theory of simulation data to fit $F(\phi)$ at zero Reynolds number

Kim & Russel, 1985

Accurate up to $\phi = 0.1$

$$F(\phi) = (1 - \phi) \left[1 + \frac{3}{\sqrt{2}} \phi^{\frac{1}{2}} + \frac{135}{64} \ln \phi + 16.456 \phi + \dots \right]$$

Brinkman, 1947

Diverges for $\phi = 0.667$

$$F(\phi) = (1 - \phi) \left[1 + \frac{3}{4} \phi \left(1 - \frac{\sqrt{8}}{\phi} - 3 \right) \right]^{-1}$$

Carman-Kozeny, 1937


Does not approach 1 for $\phi \rightarrow 0$

$$F(\phi) = 10 \frac{\phi}{(1 - \phi)^2}$$

Van der Hoef, Beetstra & Kuipers, 2005

$$F(\phi) = \frac{10\phi}{(1 - \phi)^2} + (1 - \phi)^2 \left[1 + \frac{3}{2} \sqrt{1 - \phi} \right]$$

Approach



Approach

- Now, expand to higher Reynolds numbers. A drag model based on experimental data is that of **Ergun**

We model the pressure drop based on a laminar and turbulent contribution

$$-\Delta p = A \frac{\phi^2}{(1-\phi)^3} \frac{\mu u}{d^2} + B \frac{\phi}{(1-\phi)^3} \frac{\rho u^2}{d}$$

Calibrated with experimental data gives: $A = 150$, $B = 1.75$

This is known as the “**Ergun Equation**”

We now use the ansatz: $-\Delta p = \frac{\phi}{1-\phi} \frac{18\mu u}{d^2} F$

...to arrive at the dimensionless form of the Ergun equation:

$$F(\phi, Re) = 8.33 \frac{\phi}{(1-\phi)^2} + \frac{0.097}{(1-\phi)^2} Re$$

- Unfortunately, this relationship does not hold for dilute systems (check the limiting F !)

Approach

9. Next attempt: Postulate a law of the form (motivated by Richardson-Zaki experimental data)

$$F(\phi, Re) = F(0, Re)(1 - \phi)^{-\beta}$$

Wen & Yu (1966) $\beta = 3.7$

Di Felice (1994) $\beta = 3.7 - 0.65 \exp \left[\frac{(1.5 - \log(Re))^2}{2} \right]$

10. Recent simulations show, that such a structure is **not accurate enough**. An improved and widely accepted model is:

$$F = \left[F_0(\phi) + G_{0,i}(\phi, Re_{p,i}) \right]$$

$$F_0(\phi_p) = \frac{10 \phi}{(1 - \phi)^2} + (1 - \phi)^2 (1 + 1.5 \sqrt{\phi})$$

$$G_{0,i}(\phi, Re_{p,i}) = \frac{0.413 Re_{p,i}}{24 (1 - \phi)^2} \left[\frac{(1 - \phi)^{-1} + 3\phi (1 - \phi) + 8.4 Re_{p,i}^{-0.343}}{1 + 10^{3\phi} Re_{p,i}^{-(1+4\phi)/2}} \right]$$

Beetstra et al.,
2007

Summary

1. The drag force on a single particle in a dense flow is modelled with

$$\mathbf{f}_{D,i} = V_{p,i} \beta_{p,i} \left(\langle \mathbf{u}_{f,i} \rangle - \mathbf{u}_{p,i} \right)$$

$$\beta_{p,i} = \frac{18 \eta_f}{d_{p,i}^2} (1 - \phi) F$$

This is the **filtered**
(NOT superficial)
fluid velocity

2. This is the drag force only. The **pressure gradient force** must be added in addition. In absence of other forces (e.g., gravity), the pressure gradient is

$$\sum_i \mathbf{f}_{D,i} = (1 - \phi) \nabla P$$

Outlook

3. We have discussed static particle beds. If individual particles have relative motion, so called “**fluid-mediated particle-particle**” drag forces need to be considered under certain circumstances.

$$\mathbf{f}_{D,i} = -\beta_i \Delta \mathbf{U}_i - \sum_{i \neq j} \beta_{ij} (\Delta \mathbf{U}_j - \Delta \mathbf{U}_i)$$

4. All we have discussed above is valid for mono-disperse suspensions. **For polydisperse systems, the expressions become significantly more complex.** A good model is that of Beetstra et al. (2007) and **Holloway et al. (2010)**. Essentially, those authors use a dimensionless particle size y_i (the reference being the Sauter diameter) to compute the dimensionless drag force:

$$F_{D,i-fixed}^* = \frac{1}{1-\phi} + \left(F_{D,mono}^* - \frac{1}{1-\phi} \right) \left[a y_i + (1-a) y_i^2 \right]$$

$$a = 1 - 2.66\phi + 9.096\phi^2 - 11.338\phi^3$$

Impressum & Disclaimer

©2015 by Stefan Radl, and other members of the „Simulation Science“ Group at the Institute of Process and Particle Engineering, Graz University of Technology.

All rights reserved. No part of the material protected by this copyright notice may be reproduced or utilized in any form or by any means, electronically or mechanically, including photocopying, recording or by any information storage and retrieval system without written permission from the author.

LIGGGHTS® is a registered trade mark of DCS Computing GmbH, the producer of the LIGGGHTS® software. CFDEM® is a registered trade mark of DCS Computing GmbH, the producer of the CFDEM®coupling software. This offering is not approved or endorsed by DCS Computing GmbH, the producer of the LIGGGHTS® and CFDEM® coupling software and owner of the LIGGGHTS and CFDEM® trade marks.