


SBE19
Graz

SUSTAINABLE BUILT ENVIRONMENT D-A-CH CONFERENCE 2019
Graz University of Technology, Austria
11 - 14 September 2019



COOPERATION WITH
ETH zürich **KIT**



TRINIUS Life Cycle Performance
Sustainable Construction

Declaration of the End-of-Life for Building Products

Presentation within the Special Session: End-of-Life Information

Julia Goerke
thinkstep AG

Dr. Wolfram Trinius
Ingenieurbüro Trinius GmbH

13th September 2019

Copyright (c) (2019) thinkstep – All rights reserved



The content of this presentation is generated based on an R&D project initiated and supported by the German Environment Agency (Umweltbundesamt).

Agenda

Introduction of End-of-Life Declarations (EoLD)

- Why EoLD?
- Where is the EoLD information used?
- What is the content of an EoLD?
- How does an EoLD look like?
- Who is the user of an EoLD?
- Who can benefit from EoLD?

2




TRINIUS Life Cycle Performance
Sustainable Construction



Why End-of-Life Declaration (EoLD)?

Finding the way between deconstruction and recycling



Finding the way to the recycler




TRINIUS Life Cycle Performance Sustainable Construction



Where is the EoLD information used?

In the context of EPDs and LCA for buildings & products



TRINIUS Life Cycle Performance Sustainable Construction


PRODUCT STAGE			CONSTRUCTION PROCESS STAGE		USE STAGE							END OF LIFE STAGE				BENEFITS AND LOADS BEYOND THE SYSTEM BOUNDARIES
Raw material supply	Transport	Manufacturing	Transport from the gate to the site	Assembly	Use	Maintenance	Repair	Replacement	Refurbishment	Operational energy use	Operational water use	De-construction demolition	Transport	Waste processing	Disposal	Reuse-Recovery-Recycling-potential
A1	A2	A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D

What is the content of an EoLD?

Document and dataset



- They provide the LCA results for the end-of-life of a building product or demolition material.
- The EoLD are stand-alone declarations/documents/datasets that provide the information needed for modules C and D of an EPD.
- The EoLDs are created by the recycling and disposal companies.
- Besides the LCA results they contain additional data that describe the requirements of the recycling process (delivery condition, impurities and contaminations, logistical aspects).



5

Example of how an EoLD looks like



ENVIRONMENTAL END-OF-LIFE DECLARATION

NAME AND ADDRESS OF COMPANY Company

DESCRIPTION OF THE TYPE OF DISPOSAL / RECYCLING PROCESS Mineral construction waste recycling

DEMOLITION / WASTE MATERIAL Mineral construction waste

WASTE CODE 17 01 07
Mixtures of concrete, bricks, tiles and ceramics other than those mentioned in 17 01 06 and containing dangerous substances.

SPECIFICATION FOR ASSIGNMENT TO MODULE C3 OR C4 C1

REGION DE

INPUT MATERIAL Mineral construction waste according to acceptance criteria

OUTPUT MATERIAL The final products are RC sand 0/5 (recycling sand) and RC-mix 0/32 (concrete / brick), quality controlled and certified mineral replacement building material (certificates 12-2017 / 4118-86-503)

ACCEPTANCE CRITERIA Accepted are building materials that mainly consist of natural rocks and minerals. These include: granite, masonry (made of sand-lime brick, etc.), bricks, roof tiles, composite bricks, concrete, (also reinforced concrete with and without reinforcement), porcelain.

CRITERIA FOR ACCEPTANCE EXCLUSION Construction waste with impurities (over 20%), as well as material with water polluting or chemical impurities is not accepted. These include: wood, paint residues, paints and coatings, wallpaper, building chemicals,

adhesive and carpet residues, sealants, packaging materials (paper and plastic).

INFORMATION / REQUIREMENTS FOR REMOVAL (C1) Building demolition

INFORMATION ON LOGISTICS, TRANSPORTS (C2) Delivery is by truck

INFORMATION ON REUSE, RECOVERY OR RECYCLING POTENTIAL MODULES (D) Potential benefit is declared for the substitution of RC-Sand 0/5 (recycling sand) and RC-Mix 0/32 (concrete / brick).

END OF WASTE STATUS DEFINITION A mechanical pre-sorting according to the acceptance criteria is required before delivery.

REFERENCE FLOW 1 t

SYSTEM BOUNDARY AND ASSUMPTIONS LCA information


LCA RESULTS

Parameter	UM	CR	CD	CI	CA	CC
Share organic materials	% CO-042	NO	NO	NO	NO	NO
Chloride content of the demolition waste	% Cl-011-041	NO	NO	NO	NO	NO
Asbestos content of soil and water	% P-001-041	NO	NO	NO	NO	NO
Bituminous content	% B-001-041	NO	NO	NO	NO	NO
Formation potential of greenhouse gases (global warming potential)	% GWP-041	NO	NO	NO	NO	NO
Acid equivalent content for soil-pH neutralization	% S-041	NO	NO	NO	NO	NO
Acid equivalent content for water neutralization	% W-041	NO	NO	NO	NO	NO




Who is the user of an EoLD?

Harmonised format for communication between the acteurs



7



TRINIUS Life Cycle Performance Sustainable Construction



Who can benefit from EoLD?


From module A1-D:

- Recycling companies
- Building product manufacturer (information for waste/secondary material)
- Acteurs in module B (avoidance of impurities)
- LCA practitioners
- Building planer
- Sustainable building certification schemes
- Product TCs in the context of c-PCR development
- standardization bodies

8




TRINIUS Life Cycle Performance Sustainable Construction




The EoL solution

EoLDs support the communication



I found my way to the recycler!



TRINIUS Life Cycle Performance Sustainable Construction



Thank you and any questions?




Julia C. Goerke

thinkstep AG,
Hauptstraße 111 – 113,
70771 Leinfelden-Echterdingen,
Germany



Dr. Wolfram Trinius

Ingenieurbüro Trinius GmbH,
Barmbeker Str. 9a,
22303 Hamburg
Germany



TRINIUS Life Cycle Performance Sustainable Construction

The content of this presentation is generated based on an R&D project initiated and supported by the German Environment Agency (Umweltbundesamt).

